



# SKID LOADER

**2200R**



## KEY FEATURES

- ▲ Multi-Tach® Attachment System (Universal-Type)
- ▲ Hydraloc™ System
- ▲ ROPS/FOPS Level II
- ▲ Dual T-Bar, Hand/Foot or Joystick Control System
- ▲ Zero Maintenance Axles w/8-Bolt Rims
- ▲ Acoustical Sound Material and Deluxe Headliner
- ▲ Standard High Back Cushion Seat
- ▲ Entry / Exit Grab Handles

## KEY SPECIFICATIONS

- ▲ Operating capacity (50%) – 2,200 lbs. (998 kg)
- ▲ Overall height to top of ROPS – 81" (2057 mm)
- ▲ Gross Power – 72 hp (53.7 kW) @ 2500 rpm
- ▲ Yanmar / 4TNV98CT-NMS / Tier IV / Stage 3B
- ▲ 217 ft.-lbs. (294 Nm) @ 1625 rpm max torque
- ▲ 123" (3124 mm) height to hinge pin
- ▲ 67.4" (1712 mm) machine width - less bucket
- ▲ 7,980 lbs. (3620 kg) operating weight



# SKID LOADER

## 2200R

### SPECIFICATIONS

		IMPERIAL	METRIC
DIMENSIONS	Overall Operating Height - Fully Raised	161"	4089 mm
	Height to Hinge Pin - Fully Raised	123"	3124 mm
	Overall Height to Top of ROPS	81"	2057 mm
	Overall Length with Bucket (w/o Counterweight)	136.5"	3467 mm
	Dump Angle at Full Height	40°	
	Dump Height - Fully Raised	94"	2388 mm
	Dump Reach at Full Height	27"	686 mm
	Maximum Rollback Angle at Ground	28°	
	Rollback Angle at Full Height	95°	
	Seat to Ground Height	40"	1016 mm
	Wheelbase	43"	1092 mm
	Overall Width - Less Bucket <sup>A</sup>	67.4"	1712 mm
	Bucket Width	70"	1778 mm
	Ground Clearance to Chassis	8"	203 mm
	Overall Length without Bucket (w/o Counterweight)	105"	2667 mm
	Rear Departure Angle	25°	
	Clearance Radius - Front with Bucket	87.5"	2223 mm
	Clearance Radius - Front without Bucket	52"	1321 mm
	Clearance Radius - Rear (w/o Counterweight)	60"	1524 mm
	Standard Specification Tire Size	12.00x16.5 HD	
ENGINE	Make	Yanmar	
	Model	4TNV98CT-NMS Tier IV / Stage 3B	
	Gross Power @ 2500 rpm	72 hp	53.7 kW
	Net Power @ 2500 rpm	70.7 hp	53.7 kW
	Maximum Torque @ 1625 rpm	217 ft-lbs.	294 Nm
	Displacement	202.6 cu.in.	3.3 L
HYDRAULICS	Auxiliary Hydraulic Flow - Standard	23.5 gpm	90 L/min
	High-Flow Auxiliary Hydraulics - Option	35 gpm	132.5 L/min
	Reservoir Capacity	8 gal	30.3 L
ELECTRICAL	Battery	12-volt	950 CCA
	Starter	12-volt	3.0 kW
	Alternator	100-amp	
CAPACITIES / WEIGHTS	Rated Operating Capacity <sup>B</sup>	2,200 lbs.	998 kg
	Rated Operating Capacity with Optional Counterweight <sup>B</sup>	2,370 lbs.	1075 kg
	Fuel Tank	18 gal.	68.1 L
	Travel Speed - Maximum	8 mph	12.9 km/hr
	Travel Speed with Two-Speed Option - Maximum	11.9 mph	19.2 km/hr
	Operating Weight <sup>C</sup> - Approximate	7,980 lbs.	3620 kg
SOUND / VIBRATION*	Noise Level / Environmental Level	101 dB	
	Operator Ear	85 dB	
	Hand / Arm Vibration	1.50 m/s <sup>2</sup>	
	Whole Body Vibration	.96 m/s <sup>2</sup>	

\* Standard seat option and T-Bar controls

<sup>A</sup> Overall width is dependent upon the amount of wheel offset

<sup>B</sup> Per SAE J8181, SAE J732, and ISO 14397

<sup>C</sup> Weight of base unit with standard equipment, standard tires (heavy-duty flotation), standard dirt-construction bucket and 175 lbs. (79 kg) operator.

### STANDARD FEATURES

- ▲ Control type: Dual T-Bar, Hand/Foot or Joystick
- ▲ Adjustable Control Pods
- ▲ Fuel Gauge with Real Time Fuel Consumption
- ▲ Multi-Tach® Attachment System (Universal-Style)
- ▲ Warning Lamps and Buzzer - Engine and Hydraulic Oil Temperature
- ▲ Battery Charge Indicator Lamp
- ▲ Low Oil Pressure Light and Buzzer
- ▲ Seatbelt Indicator Lamp and Buzzer
- ▲ Coolant Temperature Gauge
- ▲ Hourmeter
- ▲ Manual-Control Hydrostatic Drive
- ▲ ROPS/FOPS - Level II - Approved Overhead Guard
- ▲ Operator Restraint Bar with Armrests
- ▲ Independent Hydraulic Reservoir and Hydraulic Oil Cooler
- ▲ Engine Intake Air Pre-Heater Starting Assist
- ▲ Adjustable Seatbelt
- ▲ Lift Arm Support Device
- ▲ Hydraloc™ System
- ▲ Dual Front and Rear Work Lights
- ▲ Dual, Integral Cleanout Plates
- ▲ Vandalism Lock Provisions - Fuel and Engine Cover
- ▲ Acoustical Sound Material and Deluxe Headliner
- ▲ Deluxe High Back, Cushion Seat
- ▲ Front Auxiliary Hydraulics with 3/4-inch Flat-Faced Couplers
- ▲ Visual Hydraulic Filter Indicator
- ▲ Power Plug (12 V)
- ▲ Horn

### OPTIONAL FEATURES

- ▲ Hydraglide™ Ride Control System
- ▲ Power-A-Tach® - Hydraulic Powered Attach System
- ▲ Switchable Self-Leveling Hydraulic Lift Action
- ▲ Engine Block Heater
- ▲ Suspension Seat
- ▲ Cab Door with Wiper
- ▲ Sliding Side Windows
- ▲ Sub-Zero Crankcase Kit
- ▲ Heater/Defroster
- ▲ Bluetooth Radio & Speakers
- ▲ 3-inch Wide Seatbelt - When Required by Law
- ▲ Audible Back-Up Alarm
- ▲ Rear View Mirror
- ▲ Rear Camera - Includes 5" (127 mm) Display
- ▲ Engine Auto-Shutdown System
- ▲ Interior Dome Light
- ▲ Centrifugal Pre-Cleaner
- ▲ Rotating Beacon
- ▲ Impact-Resistant Door
- ▲ Lift Kit - Single Point Lift System
- ▲ Rear Counterweight (increases Rated Operating Capacity by 210 lbs. (95 kg) and adds 2.25" (57 mm) to length)
- ▲ Bucket Bolt-On Cutting Edge
- ▲ Easy Manager Telematics
- ▲ Battery Disconnect Switch
- ▲ Work Light Kit (LED)



MUSTANG MFG.

**MUSTANG**  
BY MANITOU

mustang-by-manitou.com

*Mustang by Manitou reserves the right to add improvements or make changes in features and specifications at any time without notice or obligation.*

*Mustang by Manitou reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly.*

One Gehl Way, West Bend, WI 53095 | Phone: (262) 334-9461